

# Degreaser WB 200

Degreasers/Cleaners

08/11/2019

L4.03.05 UK &amp; Ireland

## DESCRIPTION

The purpose of cleaning and degreasing is to remove contamination such as, residual grease, oil, wax, silicones, etc. If omitted, loss of adhesion or blistering will occur, therefore before sanding and painting always clean the object with a degreaser.

Lesonal Degreaser WB 200 is capable of removing water dissoluble contamination.

Use WB 200 after cleaning with other Lesonal Degreasers

## PRODUCT AND ADDITIVES

Product	Degreaser WB 200
---------	------------------

## METHOD OF USE

Suitable for	Existing finishes, including thermoplastic acrylics Plastic parts Primers, surfacers and fillers
--------------	--

Method of use	Wet a clean cloth thoroughly with Degreaser WB 200 and degrease / clean the surface. Subsequently dry the surface by use of another clean dry cloth.
---------------	---

Note: Never use Degreaser WB 200 on polyester putties

Product storage	Avoid extreme temperature fluctuation and high humidity levels
-----------------	--

Shelf life	3 years at 20°C
------------	-----------------

VOC	2004/42/IIIB(a)(200)200 The EU limit value for this product (product category : IIB.a) in ready to use form is max. 200 g/l VOC. The VOC content of this product in ready to use form is max. 200 g/litre.
-----	--

# Degreaser WB 200

Degreasers/Cleaners

08/11/2019

L4.03.05 UK &amp; Ireland

**Akzo Nobel Coatings LTD**  
**Address:** Unit 2B, Didcot Park  
Churchward, Southmead Industrial Estate  
Didcot, Oxfordshire, OX11 7HB  
**Tel:** 00 44 (0)1235 862226

## FOR PROFESSIONAL USE ONLY

IMPORTANT NOTE: The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfil the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give, or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advices given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.

Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.

Head Office  
Akzo Nobel Car Refinishes B.V., PO Box 3 2170 BA Sassenheim, The Netherlands. [www.Lesonal.com](http://www.Lesonal.com)